

# G-PVC/2

## Adhesive & Sealer for PVC Gutters

**Description:** High viscous PVC adhesive for bonding and sealing of rigid PVC Gutters. For use in agriculture for the "Soilless Growing Systems".

**Features:** Durable fast drying constructive adhesive. Intended for long-term use in extreme weather conditions. Water and chemical resistant. It's easy to apply with a squeezable bottle.

**Bonds:** Rigid and semi rigid PVC, C-PVC, U-PVC.

### **Physical Properties:**

Base: Synthetic copolymers.

Viscosity: 17000 CPS  $\pm 2\%$ .

Solid contents: 30%  $\pm 2\%$ .

Specific gravity: 1.01 gr./cm<sup>3</sup>.

Flash point: -20°C.

Bonding range: 1- 24 hours.

Coverage: 20-30 gr. per connector.

Color: Light blue.

Cleaning and diluting: Adhestick G-PVC Thinner.

Storage: 12 months at 20°C.

Packaging: 1 liter PE squeezable bottle.

### Application information:

1. Surfaces must be dry, clean and dust free.
2. Apply uniform layer of adhesive on one side and glue together within a short period of time.
3. Apply constant pressure while drying.
4. Let dry for 24 hours, before hanging.
5. After drying, the adhesive layer continues to strengthen.
6. Clean hands with Acetone.

**Precautions:** Refer to Material Safety Data Sheet before using this product.

**Note** Bonding trials should be carried out in the presence of our representative to obtain the best solutions. The information supplied here, is based on laboratory tests and its purpose is to assist the user in finding the optimal solution for his needs. "ADHESTICK" Ltd. or any of its employees will not be responsible for the outcome of the use of either the information supplied or the products described in this Technical Data Sheet.